

Commercial HVAC

Combustion & Emissions Analyzers Selection Guide



PARAMETERS	S1500-NP	S1500-P	S500-3	S500-3P	S4500-3	S4500-4
# of Gases	2	2	2-3	2-3	3-4	4
O ₂ Long Life, 0 - 25.0%	✓	✓	-	-	✓	✓
O ₂ Standard, 0 - 25.0%	-	-	✓	✓	-	-
CO, (Calculated from O ₂), 0 - 100%	✓	✓	✓	✓	✓	✓
CO Measurement w/NOx filter, 0 - 8000 ppm	✓	✓	-	-	✓	✓
CO Auto Dilution (0 - 10%) High Range	✓	✓	-	-	✓	✓
NOx included 5,000 ppm	-	-	✓	✓	✓	✓
Low-NOx Capable 0 - 500.0 ppm	-	-	-	-	✓	✓
TOTAL NOx (NO + NO ₂ Included)	-	-	-	-	-	✓
Ambient Temperature Measurement	✓	✓	✓	✓	✓	✓
Stack Temperature Measurement	✓	✓	✓	✓	✓	✓
Differential Pressure Manometer	✓	✓	✓	✓	✓	✓
Draft Measurement	✓	✓	✓	✓	✓	✓
Excess Air Measurement	✓	✓	✓	✓	✓	✓
Ambient CO Monitor	✓	✓	✓	✓	✓	✓
Capable of measuring NO ₂ , SO ₂ , CxHy	-	-	-	-	-	✓
High Altitude Adjustment	✓	✓	✓	✓	✓	✓
FEATURES						
Built-In Printer (Non-Fading Paper)	-	✓	-	-	✓	✓
Wireless Bluetooth® Printer	Optional	✓	Optional	✓	-	-
FIELD-REPLACEABLE Pre-Calibrated Sensors	✓	✓	✓	✓	✓	✓
Mobile App + QR code	✓	✓	(*)	(*)	✓	✓
PC Software	✓	✓	-	-	✓	✓
Automatic data Logging	✓	✓	✓	✓	✓	✓
Combustion Efficiency Measurements for All Atmospheric & Condensing Systems	✓	✓	✓	✓	✓	✓
Internal Memory (# of Tests)	2000	2000	5	5	2000	2000
Rechargeable Battery w/ AC Charger	✓	✓	✓	✓	✓	✓
Display Screen	Multicolor	Multicolor	One color	One color	Multicolor	Multicolor
Carrying Case	Hard	Hard	Hard	Hard	Hard	Hard

(*): Mobile App only for QR code

SEITRON AMERICAS INC.

4622 E. Street Road

Treose, PA 19053 - USA

Phone (215) 660-9777 - Fax (215) 660-9770

info@seitronamericas.com - www.seitronamericas.com

